

Available Sizes

6'x10' SA 6'x12' TA 6'x14' TA

Structure

Aluminum tube frame (floor, walls, & ceiling)
 16" o/c walls & roof supports / 24" o/c Floors
 Integrated main frame
 24" V-nose
 2" coupler
 2000# tongue jack
 Smooth aluminum fenders

Axles

Dexter spring axle 3500#

Tire / Wheels

Silver mod wheels with radial tires

Doors

32"x74" Side entry door with flush lock
 Rear ramp door with spring assist

Electrical

Clear LED marker & break lights
 1 Interior dome light with intergraded switch
 Interior mounted battery & junction box
 4 way flat plug

Exterior

Screwless .030 bonded aluminum skin
 Screwless 3" upper rub rail
 Seamless one-piece aluminum roof (triple sealed)
 24' ATP Stoneguard
 2 Side wall vents
 Aluminum grab handles
 48" Aluminum bar locks with grease fitting (ramp door)
 Aluminum door hinges

Interior

3/4" Water resistant flooring
 3/8" Water resistant walls
 ATP Interior cove trim



Trailer Model

DBET 6x10 SA

DBET 6x12 SA

DBET 6x12 TA

OVERALL LxWxH	13'8" x 102"x 8'3"	15'8" x 102"x 8'2"	15'8" x 102"x 8'3"
BOX LxWxH	10' x 72"x 86"	12' x 72"x 86"	12' x 72"x 86"
INTERIOR LxWxH	11'8" x 69"x 78"	13'8" x 69"x 78"	13'8" x 69"x 78"
V-NOSE	2'	2'	2'
PLATFORM HEIGHT	17"	17"	17"
REAR DOOR WXH	64" x 76"	64" x 76"	64" x 76"
HITCH HEIGHT	16" top of ball	16" top of ball	16" top of ball
HITCH BALL SIZE	2"	2"	2 5/16"
HITCH RATING	5000#	5000#	11000#
GVWR	2990#	2990#	7000#
CURB WEIGHT	1000#	1100#	1250#
PAYLOAD	1990#	1890#	5750#
AXLE TYPE	Spring	Spring	Spring
AXLE RATING	3500#	3500#	3500#
AXLE QUANTITY	1	1	2
TIRES	205/75R15	205/75R15	205/75R15
WHEELS	Silver Mod	Silver Mod	Silver Mod