

Available Sizes

6'x10' SA 6'x10' SA 6'x12' TA

Structure

Aluminum tube frame (floor, walls, & ceiling)
 16" o/c floor, walls & roof supports
 Integrated main frame
 24" V-nose
 2" coupler
 2000# tongue jack
 Smooth aluminum fenders

Axles

Dexter torsion ride 3500#

Tire / Wheels

Silver mod wheels with radial tires

Doors

32"x74" Side entry door with flush lock
 Rear ramp door with spring assist

Electrical

Clear LED marker & break lights
 1 Interior dome light with wall switch
 Interior mounted battery & junction box
 4 way flat plug

Exterior

Screwless .030 bonded aluminum skin
 Screwless 3" upper rub rail
 Seamless one-piece aluminum roof (triple sealed)
 24' ATP Stoneguard
 2 Side wall vents
 Aluminum grab handles
 48" Aluminum bar locks with grease fitting (ramp door)
 Aluminum door hinges

Interior

3/4" Water resistant flooring
 3/8" Water resistant walls
 ATP Interior cove trim



| Trailer Model | DBET 6x10 SA | DBET 6x12 SA | DBET 6x12 TA |
|-----------------|---------------------|---------------------|---------------------|
| OVERALL LxWxH | 13'8" x 102" x 8'3" | 15'8" x 102" x 8'2" | 15'8" x 102" x 8'3" |
| BOX LxWxH | 10' x 72" x 86" | 12' x 72" x 86" | 12' x 72" x 86" |
| INTERIOR LxWxH | 11'8" x 69" x 78" | 13'8" x 69" x 78" | 13'8" x 69" x 78" |
| V-NOSE | 2' | 2' | 2' |
| PLATFORM HEIGHT | 17" | 17" | 17" |
| REAR DOOR WXH | 64" x 76" | 64" x 76" | 64" x 76" |
| HITCH HEIGHT | 16" top of ball | 16" top of ball | 16" top of ball |
| HITCH BALL SIZE | 2" | 2" | 2 5/16" |
| HITCH RATING | 5000# | 5000# | 11000# |
| GVWR | 2990# | 2990# | 7000# |
| CURB WEIGHT | 1000# | 1100# | 1250# |
| PAYLOAD | 1990# | 1890# | 5750# |
| AXLE TYPE | Torsion | Torsion | Torsion |
| AXLE RATING | 3500# | 3500# | 3500# |
| AXLE QUANTITY | 1 | 1 | 2 |
| TIRES | 205/75R15 | 205/75R15 | 205/75R15 |
| WHEELS | Silver Mod | Silver Mod | Silver Mod |